

TECHNICAL DATA SHEET

Effective From: 14th Aug. 2020

PRODUCT CODE: B 1488 G	COMMERCIAL NAME: Top Coat, Clear, Matt, Base
DESCRIPTION: Two-components matt polyurethane transparent varnish	

PROPERTIES

Recommended for / Main area of application	Universal matt polyurethane varnish with excellent transparency, filling, excellent verticality and softness to the touch.
Recommended for / Main area of application	The high wetting and expanding properties, make it suitable for flat surfaces, assembled furniture and doors for interior use.
Application Method	By spray, airless, curtain coater
Shelf life	1 year

APPLICATION PROPERTIES		PHISICAL PROPERTIES	
Coverage Area	75-87 sqft/lit/coat	Viscosity	84" +/- 8" DIN 4
Vertical Stability	--	Solid Content	42 +/- 2%
Hardener	H 80 50%	Specific Weight	0.980 +/- 0.030 Kg/Lt
Thinner	T 1460 20 - 30%	Glossy	30 +/- 3 G
Pot Life	> 4 h	Ph	-

GENERAL INFORMATION			
Drying at 20°C		Oven Drying	
Dust Free	10-15min	Time for Flash Off	-
Touch Free	60min		
Sanding	-	Time for drying	-
Overcoating	-		
Stackable	6-8 h	Time for cooling	-

A Jubilant Industries Company

OUR VALUES



Jubilant Agri & Consumer Products Ltd.
C-26, Sector 59,
Noida-201 301, UP, India
Tel: +91 120 4362205
Fax: +91 120 2580033
www.jacpl.co.in

Corporate Office:
Plot No.# 15, Knowledge Park - II,
Greater Noida, Distt. Gautam
Budh Nagar - 201 306, UP, India
Tel : +91 120 7186000
Fax : +91 120 7186040, 7186140

Regd Office:
Bhartiagram, Gajraula
Distt. Amroha-244 223,
UP, India

*This product is Implored from Verinlegno - Italy



TECHNICAL DATA SHEET

Effective From: 14th Aug. 2020

RECOMMENDED APPLICATION PROCESS

After 10-30 min apply two coats, 40-60 min from each other of transparent polyurethane sealer, suggested SB 1784- Sealer, Clear, Base. After 8 - 12 h sand with sand paper 240 - 400 and apply by spray 75-87 sqft/lit/coat 1488 G - Top Coat, Clear, Matt, Base, and hardener at 50% with H 80 and thinned at 20-30% with T 1460.

NOTES	User is responsible to make the application of the product in a place with an adequate air- recycle and on respecting of all hygienic and safety regulations.
STORAGE	Containers must be stored tightly closed in a well-ventilated place with temperatures between 5° C and 35°C.

A Jubilant Industries Company

OUR VALUES



Jubilant Agri & Consumer Products Ltd.
C-26, Sector 59,
Noida-201 301, UP, India
Tel: +91 120 4362205
Fax: +91 120 2580033
www.jacpl.co.in

Corporate Office:
Plot No.# 15, Knowledge Park - II,
Greater Noida, Distt. Gautam
Budh Nagar - 201 306, UP, India
Tel: +91 120 7186000
Fax: +91 120 7186040, 7186140

Regd Office:
Bhartiagram, Gajraula
Distt. Amroha-244 223,
UP, India

*This product is Implored from Verinlegno - Italy

