

## TECHNICAL DATA SHEET

Effective From: 14th Aug. 2020

<b>PRODUCT CODE: B 1488 G</b>	<b>COMMERCIAL NAME: Top Coat, Clear, Matt, Base</b>
<b>DESCRIPTION: Two-components Polyurethanic transparent top-coat</b>	

### PROPERTIES

<b>Recommended for / Main area of application</b>	Universal matt polyurethane varnish with excellent transparency, filling, excellent verticality and softness to the touch. The high wetting and expanding properties, make it suitable for flat surfaces, assembled furniture and doors for interior use.
<b>Application Method</b>	Spray, airless, curtain coater
<b>Shelf life</b>	1 year

APPLICATION PROPERTIES		PHISICAL PROPERTIES	
<b>Coverage Area</b>	75-87 sqft/lit/coat	<b>Viscosity</b>	90" +/- 8" DIN 4
<b>Vertical Stability</b>	--	<b>Solid Content</b>	42 +/- 2%
<b>Hardener</b>	H 80 50%	<b>Specific Weight</b>	0.980 +/- 0.030 Kg/Lt
<b>Thinner</b>	T 1460 20 - 30%	<b>Glossy</b>	10 +/- 3 G
<b>Pot Life</b>	> 4 h	<b>Ph</b>	-

GENERAL INFORMATION			
Drying at 20°C		Oven Drying	
<b>Dust Free</b>	10-15min	<b>Time for Flash Off</b>	-
<b>Touch Free</b>	60min	<b>Time for drying</b>	-
<b>Sanding</b>	-	<b>Time for cooling</b>	-
<b>Overcoating</b>	-		
<b>Stackable</b>	6-8 h		

A Jubilant Industries Company

OUR VALUES



**Jubilant Agri & Consumer Products Ltd.**  
C-26, Sector 59,  
Noida-201 301, UP, India  
Tel: +91 120 4362205  
Fax: +91 120 2580033  
www.jacpl.co.in

Corporate Office:  
Plot No.# 15, Knowledge Park - II,  
Greater Noida, Distt. Gautam  
Budh Nagar - 201 306, UP, India  
Tel : +91 120 7186000  
Fax : +91 120 7186040, 7186140

Regd Office:  
Bhartiagram, Gajraula  
Distt. Amroha-244 223,  
UP, India

\*This product is Implored from Verinlegno - Italy



## TECHNICAL DATA SHEET

Effective From: 14th Aug. 2020

### RECOMMENDED APPLICATION PROCESS

After 10-30 min apply two coats, 40-60 min from each other of transparent polyurethane sealer, suggested SB 1784- Sealer, Clear, Base. After 8 - 12 h sand with sand paper 240 - 400 and apply by spray 75-87 sqft/lit/coat 1488 G - Top Coat, Clear, Matt, Base, and hardener at 50% with H 80 and thinned at 20-30% with T 1460.

NOTES	User is responsible to make the application of the product in a place with an adequate air- recycle and on respecting of all hygienic and safety regulations.
STORAGE	Containers must be stored tightly closed in a well-ventilated place with temperatures between 5° C and 35°C.

#### A Jubilant Industries Company

##### OUR VALUES



**Jubilant Agri & Consumer Products Ltd.**  
C-26, Sector 59,  
Noida-201 301, UP, India  
Tel: +91 120 4362205  
Fax: +91 120 2580033  
www.jacpl.co.in

Corporate Office:  
Plot No.# 15, Knowledge Park - II,  
Greater Noida, Distt. Gautam  
Budh Nagar - 201 306, UP, India  
Tel : +91 120 7186000  
Fax : +91 120 7186040, 7186140

Regd Office:  
Bhartiagram, Gajraula  
Distt. Amroha-244 223,  
UP, India

\*This product is Implored from Verinlegno - Italy

