

TECHNICAL DATA SHEET

Effective From: 14th Aug. 2020

PRODUCT CODE: B 1000 G	COMMERCIAL NAME: Top Coat, White, Glossy, Base
DESCRIPTION: Two-components white polyurethane glossy finish	

PROPERTIES

Recommended for / Main area of application	Polyurethane glossy white top coat with good filling, brightness, non-yellowing, hardness, leveling. It can be polished after 48h. Suggested to paint of kitchens doors, bathroom and indoor furniture.
Application Method	spray, airless, air mix
Shelf life	1 year

APPLICATION PROPERTIES		PHISICAL PROPERTIES	
Coverage Area	96 - 110 sqft/lit/coat	Viscosity	36" +/- 5" DIN 6
Vertical Stability	--	Solid Content	71 +/- 2%
Hardener	H 44 80-100% by weight	Specific Weight	1.390 +/- 0.050 Kg/Lt
Thinner	T 2074 30%	Glossy	98 +/- 2 G
Pot Life	> 4 h	Ph	-

GENERAL INFORMATION			
Drying at 20°C		Oven Drying	
Dust Free	30min	Time for Flash Off	-
Touch Free	2-3 h		
Sanding	-	Time for drying	-
Overcoating	Without sanding within 8 h		
Stackable	8 -12 h	Time for cooling	-

A Jubilant Industries Company

OUR VALUES



Jubilant Agri & Consumer Products Ltd.
C-26, Sector 59,
Noida-201 301, UP, India
Tel: +91 120 4362205
Fax: +91 120 2580033
www.jacpl.co.in

Corporate Office:
Plot No.# 15, Knowledge Park - II,
Greater Noida, Distt. Gautam
Budh Nagar - 201 306, UP, India
Tel: +91 120 7186000
Fax: +91 120 7186040, 7186140

Regd Office:
Bhartiagram, Gajraula
Distt. Amroha-244 223,
UP, India

*This product is Implored from Verinlegno - Italy



RECOMMENDED APPLICATION PROCESS

Sand with sand paper 220, 400 and 600 and apply by spray 96-110 sqft/lit/coat of B 1000 G-Top Coat, White, Glossy, Base. Hardener at 100% with H 44 and thinned at 30-50% with P 2074.

NOTES	User is responsible to make the application of the product in a place with an adequate air- recycle and on respecting of all hygienic and safety regulations.
STORAGE	Containers must be stored tightly closed in a well-ventilated place with temperatures between 5° C and 35°C.

A Jubilant Industries Company

OUR VALUES



Jubilant Agri & Consumer Products Ltd.
C-26, Sector 59,
Noida-201 301, UP, India
Tel: +91 120 4362205
Fax: +91 120 2580033
www.jacpl.co.in

Corporate Office:
Plot No.# 15, Knowledge Park - II,
Greater Noida, Distt. Gautam
Budh Nagar - 201 306, UP, India
Tel : +91 120 7186000
Fax : +91 120 7186040, 7186140

Regd Office:
Bhartiagram, Gajraula
Distt. Amroha-244 223,
UP, India

*This product is Implored from Verinlegno - Italy

