

TECHNICAL DATA SHEET

Effective From: 14th Aug. 2020

PRODUCT CODE: SB 454	COMMERCIAL NAME: Sealer, White, Base
DESCRIPTION: Two-component polyurethane white sealer.	

PROPERTIES

Recommended for / Main area of application	Polyurethane white sealer, specific for MDF with an excellent filling, excellent covering and good sanding properties. Suitable for over coating with glossy polyurethane varnish. Suggested to paint for bathroom furniture, kitchen furniture, wardrobes and doors for interior. Suitable for MDF and for every kind of wood.
Application Method	By spray, airless
Shelf life	1 year

APPLICATION PROPERTIES		PHISICAL PROPERTIES	
Coverage Area	72 - 84 sqft/lit/coat	Viscosity	46 " +/-5" DIN 8
Vertical Stability	--	Solid Content	77 +/-2 %
Hardener	H 36 50 % by weight	Specific Weight	1.510 +/-0.050 Kg/Lt
Thinner	T 1460 20%	Glossy	-
Pot Life	> 3 h	Ph	-

GENERAL INFORMATION

Drying at 20°C		Oven Drying	
Dust Free	10min		
Touch Free	60min	Time for Flash Off	20min a 30°-35° C
Sanding	3 - 4 h	Time for drying	20min a 45°-50°C
Overcoating	8 - 12 h		
Stackable	6 h	Time for cooling	20min a 20°-25°C

A Jubilant Industries Company

OUR VALUES



Jubilant Agri & Consumer Products Ltd.
C-26, Sector 59,
Noida-201 301, UP, India
Tel: +91 120 4362205
Fax: +91 120 2580033
www.jacpl.co.in

Corporate Office:
Plot No.# 15, Knowledge Park - II,
Greater Noida, Dist. Gautam
Budh Nagar - 201 306, UP, India
Tel: +91 120 7186000
Fax: +91 120 7186040, 7186140

Regd Office:
Bhartiagram, Gajraula
Distt. Amroha-244 223,
UP, India

*This product is Implored from Verinlegno - Italy



RECOMMENDED APPLICATION PROCESS

Apply by spray 72-84 sqft/lit/coat of SB 454 - Sealer, White, Base and Hardener at 50% in weight with H 36 and thinned at 20% with T 1460 .

After 40 – 60 min, apply a second coat of sealer, prepared as above explained.

Sand with sand paper 220-400 and apply a coat of polyurethane top coat.

NOTES	User is responsible to make the application of the product in a place with an adequate air- recycle and on respecting of all hygienic and safety regulations.
STORAGE	Containers must be stored tightly closed in a well-ventilated place with temperatures between 5° C and 35°C.

A Jubilant Industries Company

OUR VALUES



Jubilant Agri & Consumer Products Ltd.

C-26, Sector 59,
Noida-201 301, UP, India
Tel: +91 120 4362205
Fax: +91 120 2580033
www.jacpl.co.in

Corporate Office:
Plot No.# 15, Knowledge Park - II,
Greater Noida, Distt. Gautam
Budh Nagar - 201 306, UP, India
Tel : +91 120 7186000
Fax : +91 120 7186040, 7186140

Regd Office:
Bhartiagram, Gajraula
Distt. Amroha-244 223,
UP, India

*This product is Implored from Verinlegno - Italy

