



# **DIRECTIONS FOR USE**

- **SURFACE PREPARATION:** Sand the wooden surface with Emery Paper No.180 followed by Emery Paper No.220. Wipe the surface clean. For pre-polished wood, remove the coating by scraping or sanding. Apply Water Based Impregnator by brush, spray or rag for protecting the wooden surface. Do light sanding with Scotch-Brite.
- 2 SEALER APPLICATION: Apply Water Based Exterior Sealer on the above surface by brush or spray. Recoat after drying of 4-8 hours. Sand with Emery Paper No. 320/400 in between coats.
- 3 TOP COAT APPLICATION: Apply Water Based Exterior Topcoat by brush or spray. Recoat after drying of minimum 12 hours. Sand with Emery Paper No. 320/400 in between coats. Apply 2-3 coats.

For SELF SEALER INTERIOR, apply on the sanded wooden Surface by spray. Recoat after drying of minimum 12 hours. Sand with Emery Paper No. 320/400 in between coats. Apply 2-3 coats.







#### **Jubilant Agri and Consumer Products Limited**

Plot No. #15, Knowledge Park – II, Greater Noida-201306, Uttar Pradesh, India. Tel.: +91-120-7186000 Website: www.jacpl.co.in











# WATER BASE - SELF SEALER (INTERIOR GRADE)

Water Based Self Sealer is environmental-friendly and easy to use. It requires no separate sealer and also offers easy cleanability of tools, making it very user friendly.

## Technical Data (Interior)

Product	Pack Size	Application Method	Thinner	Thinner Quantity	Drying Time		Coverage	Gloss/Sheen
					Surface Dry (min)	Hard Dry (hrs)	Coverage Sq Ft/Litre/Coat	@ 60 Deg
Water Based Self Sealer Clear Matt - Interior (Gloss 10 & Gloss 30)	1 Itr	Spray	Water	0-10%	1-2 Hrs.	12 Hrs.	68-80	G10 / G30
	5 Itr							(as per grade used)
	10 Itr							



# **Luxury Water Based Wood Finish**

Ultra Italia is a Luxury Water Based Wood Finish, which enhances the beauty of the wood. It is an environmental-friendly product with low VOC odour, used to give a fine matt finish to your wood.








Exterior use



Low VOC













# WATER BASE - EXTERIOR GRADE

Water Based Impregnator protects the wooden surface and locks the tanin from the wood. The sealer has high solid content, good covering and sanding properties. The finish also has excellent filling properties and offers optimum resistance to weather exposure.

### Technical Data (Exterior)

· · · · · · · · · · · · · · · · · · ·												
	Pack	Application	Thinner	Thinner Quantity	Drying Time		Coverage	Gloss/Sheen				
Product	Size	Method	Tillillei		Surface Dry (min)	Hard Dry (hrs)	Sq Ft/Litre/Coat	@ 60 Deg				
Water Based Impregnator	1 ltr	Brush/Spray/Rag			1 Hr.	2-4 Hr.	120 - 200	Not applicable				
Water-based Clear Sealer - Exterior	5 ltr	Spray/Brush	Water	0-10%	2 Hrs.	4-8 Hrs.	40 - 50	Not applicable				
Water-based Clear Top Coat - Matt - Exterior	10 Itr	Spray/Brush			2 Hrs.	12 Hrs.	40 - 50	30				